SIVAL

ALUMINIUM SYSTEMS

SV-8000 Eco Slide

SLIDING SYSTEMS · SV-8000

SV-8000 Eco Slide series is a new Economical, Sliding system with a simple straight-line design.



THE SYSTEM

SV-8000 Eco Slide series is a new Economical, Sliding system with a simple straight-line design.

Designed to provide solutions for old doors and windows replacement as well as for new constructions, showing emphasis on modern aesthetic and functionality. The rollers slide on stainless steel lamina giving a straight smooth and easy movement of the sashes.

SV-8000 Eco Slide and SV-850 Eco have a common aesthetic design and can be combined perfectly. The milling process of the profiles is done in the cor responding punching machine.

Wide range of accessories from all major European Companies covers every possible construction of the system.

APPLICATIONS

residential | extensions | hospitality | renovation

Basic characteristics

- Modern aesthetics due to the straight-line design.
- Option for Multi-Locking Mechanism for improved safety.
- Smooth sliding with the use of stainless-steel lamina on rail profiles.
- Use of glazing up to 21mm.
- Can be combined with the SV-850 Eco opening system for complex constructions.

Technical characteristics

Aluminium alloy	EN AW 6060 T6
Hardness	12 Webster
Minimum coating thickness	75μm
Profile thickness	1,2mm
Tolerance according to	EN 12020-02
Width of successive driver	89mm (double sash)
Width of in-wall driver	113mm (glass-insect screen-shutter)
Dimensions of glass & shutter sash	34mm
Glazing thickness	up to 21mm
Maximum sash dimensions (WxH)	1,6m x 2,6m (WxH)
Maximum sash weight	100Kg

Gallery & technical drawings







+44 7426 890065 · info@sival.co.uk

Technical data per manufacturer documentation, October 2026. Performance depends on configuration and glazing.